

## DATA SHEET

### AD 1,200, DESICCANT AIR DRYER

Serial number: 121524

Length	60"
Height	88"
Width	33" (Forklift pockets access)
Weight	2300 lbs. (When full of desiccant)
Voltage	120 VAC for auto drains on the desiccant tank and afterfilter

#### Features:

- Skid mounted.
- Structural steel frame for protection of the equipment.
- Forklift pockets.
- Certified lifting eyes (4 each) for handling by overhead crane.
- AIR to AIR Heat Exchanger.
- Air powered fan motor for air-to-air heat exchanger.
- Filter/regulator/lubricator provided for air powered fan motor.
- Air motor requires 70 CFM for operation.
- Desiccant tank is ASME rated @ 200 PSI.
- System is rated for 1,200 SCFM @ 100 PSIG, 180° F.
- 2-1/2" Inlet air piping.
- 3" outlet air piping.
- Sight glass in desiccant tank for visual inspection of desiccant level.
- Manual drain and electric drain on the desiccant tank and afterfilter.

#### Notes:

1. Not intended to be laid on it side.
2. Air (bull) hoses and fittings not provided for connection of the equipment.
3. Additional charges may apply for desiccant used during the rental period.
4. Not intended to be used with air compressors with high levels of oil in the air discharge.